



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification: H04M 11/00, H04M 3/42	A1	(11) International Publication Number: WO 00/56050 (43) International Publication Date: 21 September 2000 (21.09.2000)
(21) International Application Number: PCT/IL00/00162 (22) International Filing Date: 15 March 2000 (15.03.2000) (30) Priority Data: 60/124,369 15 March 1999 (15.03.1999) US (60) Parent Application or Grant VOCALTEC COMMUNICATIONS LTD. [/]; O. FOX, Joshua [/]; O. HERTZOG, Yuval [/]; O. KORMAN, David [/]; O. KESSEL, Omri [/]; O. GIAN, Shlomi [/]; O. LAZAROVICH, Yoram [/]; O. HENDLER, Ofer [/]; O. FOX, Joshua [/]; O. HERTZOG, Yuval [/]; O. KORMAN, David [/]; O. KESSEL, Omri [/]; O. GIAN, Shlomi [/]; O. LAZAROVICH, Yoram [/]; O. HENDLER, Ofer [/]; O. EITAN, PEARL, LATZER & COHEN-ZEDEK ; O.	Published	
(54) Title: AUDIO AND DATA COLLABORATION AND COORDINATION SYSTEM (54) Titre: SYSTEME DE COORDINATION ET DE COLLABORATION DE AUDIO/DONNEES (57) Abstract <p>There is disclosed systems and methods for coordinating IP audio calls with data collaboration sessions, including voice and data, over a network, such as the Internet (24). This is accomplished by providing an identifying data field to accompany the audio call on its journey from caller (sender or client, 20) to intended recipient (receiver or agent, 22a, 22c), this identifying data field also being employed as an identifier of the corresponding data collaboration, between the caller, and the intended recipient, allowing for the parallel and coordinated transmission of voice and data over separate communication channels.</p> (57) Abrégé <p>La présente invention concerne des systèmes et des procédés de coordination de communications audio de protocole IP avec des sessions de collaboration de données, y compris voix et données, dans un réseau, tel qu'Internet (24). Pour ce faire, on fournit au destinataire (récepteur ou agent, 22a, 22c) prévu un champ de données d'identification pour accompagner dans son trajet l'appel audio en provenance de l'appelant (émetteur ou client, 20); ce champ de données d'identification étant également utilisé comme identificateur de collaboration de données correspondantes, entre l'appelant et le destinataire prévu, permettant ainsi l'émission parallèle et coordonnée de voix/données dans des canaux de communications séparés.</p>		

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : H04M 11/00, 3/42		A1	(11) International Publication Number: WO 00/56050
			(43) International Publication Date: 21 September 2000 (21.09.00)
(21) International Application Number: PCT/IL00/00162		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 15 March 2000 (15.03.00)			
(30) Priority Data: 60/124,369 15 March 1999 (15.03.99) US			
(71) Applicant (for all designated States except US): VOCALTEC COMMUNICATIONS LTD. [IL/IL]; Maskit Street 2, 46733 Herzlia (IL).			
(72) Inventors; and (75) Inventors/Applicants (for US only): FOX, Joshua [IL/IL]; Aderet Street 1041, 99850 Emek Ha'ela (IL). HERTZOG, Yuval [IL/IL]; Shay Agnon Street 1, 43380 Ra'anana (IL). KORMAN, David [IL/IL]; Hallanot Street 12, 42823 Tzoran (IL). KESSEL, Omri [IL/IL]; Hashmonaim Street 57, 65273 Tel Aviv (IL). GIAN, Shlomi [IL/IL]; Tsfat Street 6, 63143 Tel Aviv (IL). LAZAROVICH, Yoram [IL/IL]; Bet Tzuri Street 32, 69122 Tel Aviv (IL). HENDLER, Ofer [IL/IL]; Hagalil Street 49, 44233 Kfar Sava (IL).		Published With international search report.	
(74) Agent: EITAN, PEARL, LATZER & COHEN-ZEDEK; 2 Gav Yam Center, Shenkar Street 7, 46725 Herzlia (IL).			

(54) Title: AUDIO AND DATA COLLABORATION AND COORDINATION SYSTEM



(57) Abstract

There is disclosed systems and methods for coordinating IP audio calls with data collaboration sessions, including voice and data, over a network, such as the Internet (24). This is accomplished by providing an identifying data field to accompany the audio call on its journey from caller (sender or client, 20) to intended recipient (receiver or agent, 22a, 22c), this identifying data field also being employed as an identifier of the corresponding data collaboration, between the caller, and the intended recipient, allowing for the parallel and coordinated transmission of voice and data over separate communication channels.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

AUDIO AND DATA COLLABORATION AND COORDINATION SYSTEM

CROSS REFERENCES TO RELATED APPLICATIONS

This patent application claims priority from and is related to U.S. Provisional Patent Application No. 60/124,369, entitled: ENABLED CALL CENTER SYSTEM, filed on March 15, 1999, this U.S. Provisional Patent Application incorporated by reference herein.

FIELD OF THE INVENTION

The present invention is related to voice and data applications over Internet Protocol (IP) networks, and particularly to systems and methods where an audio call is coordinated with a data collaboration session over a network, such as the Internet.

BACKGROUND OF THE INVENTION

The Internet has emerged as an effective way to speed transactions and provide service to an ever growing number of users that by early 2000 is expected to exceed 47 million. Along with this growth in users, has come the growth of electronic commerce or "e-commerce", online transactions typically involving the sale of goods and services. Thousands of businesses have entered into e-commerce, realizing the lucrative profits that can be gained by reaching this Internet user population with web-based services, advertising, product promotion and sales.

In a typical e-commerce scenario, an audio call is made between a client and the agent over the Internet. This audio call typically travels through a PSTN-to-IP gateway, and then to the agent's PSTN PBX. The conventional protocols associated with this PSTN technology are limited, and thus, any accompanying data transmissions are limited, if even possible.

SUMMARY OF THE INVENTION

The present invention improves on the contemporary art by providing systems and methods for coordinating IP audio calls with data collaboration

5 sessions, including voice and data, over a network, such as the Internet. This is
accomplished by providing an identifying data field to accompany the audio call
10 on its journey from caller (sender or client) to intended recipient (receiver or
agent), this identifying data field also being employed as an identifier of the
5 corresponding data collaboration, between the caller, and the intended recipient,
allowing for the parallel and coordinated transmission of voice and data over
separate communication channels.

15 Embodiments of the present invention are directed to call center systems
that allow for data collaboration sessions, such as a web-enabled call center for
10 audio and data collaboration sessions between a sender, typically a client and a
receiver, typically a web-enabled agent, the system including means for placing
20 at least one first cosurfer identifier, i.e., an Automatic Number Identifier (ANI), in:
at least one audio component for placement in an audio call of at least one
sender; and at least one data collaboration component for placement in a data
25 call of this at least one sender.

The system also includes at least one data collaboration sever configured
for: receiving first data corresponding to the audio call from the at least one
30 sender to the at least one receiver, with this first data including at least this first
cosurfer identifier, from the at least one sender and a second cosurfer identifier,
20 from the at least one receiver, the first cosurfer identifier is different than the
second cosurfer identifier; receiving second data including the first cosurfer
35 identifier, from the data call from the at least one sender; receiving third data
including the second cosurfer identifier from a data call from the at least one
receiver; and processing this first second and third data, to connect a data call
25 between said at least one sender and at least one receiver, this data call
between the at least one sender and the at least one receiver in parallel and
coordinated with the audio call between these same parties.

40 Embodiments of the present invention are also directed to methods for
conducting audio calls and data collaboration sessions over wide area networks,
45 for example, the Internet, between a sender, typically a client and a receiver,
30 typically a web-enabled agent. These embodiments typically comprise providing
a sender with at least one audio component and at least one data collaboration
50

5 component, providing the sender with a first cosurfer identifier, i.e., an Automatic Number Identifier (ANI), and copying the first cosurfer identifier into at least one audio component and at least one data component of the at least one sender.

10 The sender then sends this first cosurfer identifier by the at least one audio component, and it joins with a second cosurfer identifier, this second cosurfer identifier being different than the first cosurfer identifier, and coming from at least one intended receiver in accordance with an audio call between the at least one sender and the at least one intended receiver. This first cosurfer identifier is then sent to at least one server by the data collaboration component in accordance with a data call. This data call from the sender is then connected with a data call from the at least one intended receiver, as a result of the receiver having transmitted this second cosurfer identifier to the at least one server. This results in a data call between the at least one sender and the at least one intended receiver in parallel and coordinated with the audio call between these same parties.

BRIEF DESCRIPTION OF THE DRAWINGS

30 Attention is now directed to the attached drawings, wherein like reference numeral or characters indicate corresponding or like components. In the drawings:

35 Fig. 1 is a diagram of an embodiment of the present invention in use in an exemplary application; and

40 Fig. 2 is a flow chart of a process useful in implementing an embodiment of the present invention.

DETAILED DESCRIPTION OF THE DRAWINGS

45 Fig. 1 shows the present invention in use, from the side of the client 20, typically the caller or sender, and the side of the agent(s) 22a-22c, typically the recipient or receiver. The client and agent sides are connected via a wide area network (WAN), typically the Internet 24.

50 From the client side, the client 20, has a multimedia PC 30 (e.g., with a Pentium® from Intel Corporation, Santa Clara, California 95052, CPU) with

5 voice and data capabilities. The multimedia PC 30 employs an operating
system such as Windows® NT® (from Microsoft Corporation, Redmond,
Washington 98052) or the like, and is equipped with a suitable modem or other
10 hardware for accessing a wide area network (WAN), here the Internet 24. The
5 PC 30, with monitor 31, is also loaded with software that operates as a browser
for the internet, exemplary browsers suitable for use here including Microsoft®
Internet Explorer® (Microsoft Corporation, Redmond, WA) and Netscape®
15 Navigator® and Netscape® Communicator®, the later two from Netscape
Communications Corporation, Mountain View, California 94043.

10 On the agent side, are web enabled agents 22a-22c. While three agents
are shown, this is exemplary only, for any number of agents (one or greater) is
20 permissible in accordance with the present invention. These agents 22a-22c
are typically equipped with multimedia PC's 32 with voice and data capabilities,
and include browsers, in accordance with those detailed above. Each agent
25 15 22a-22c uses a regular (POTS) telephone for audio, typically voice. The PC's of
the agents 22a-22c have a connection to the WAN, here the Internet 24 for data,
and connect to a Private Branch Exchange System (PBX) 36 for voice.

30 The PBX system (PBX) 36 connects to the Internet 24, typically through a
gatekeeper 38. For example, one gatekeeper 38 may be a VocalTec®
20 Gatekeeper®, from VocalTec Communications, Ltd., Herzlia 46733, Israel,
although a gatekeeper is not necessary.

35 Within the PBX 36 is an automatic call distribution unit (ACD) 40, that
functions as a switch, to route voice calls to the selected agent 22a-22c, typically
the first available agent. For example, one ACD suitable for use with this system
25 40 is a DEFINITY G3 ACD from Lucent Technologies, Murray Hill, New Jersey.

45 The PBX connects to a Telephony Server (T-server) 42, that is configured
to convert PBX telephony data into Internet Protocol (IP) data. For example, a
suitable T-server for use with this system is a PacketStar™ Internet Telephony
Server from Lucent Technologies, Murray Hill, New Jersey.

30 50 The T-server 42 connects to a Data Collaboration (DC) Server 44 that in
turn, connects to the Internet 24. The DC server 44 typically includes a
co-resident Computer Telephone Integration (CTI) driver 45. The DC server

5 provides the interface between an incoming client (customer) call, telephony gateway terminals and call center equipment, such as the ACD/switch, and the Internet 24. For example, the DC server and CTI driver are available as a
10 VocalTec® Surf & Call™ Server (available from VocalTec Communications, Ltd., Herzlia, Israel).

5 Servers 1 and 2, indicated as 50, 52, are connected to the Internet 24. These servers 50, 52 are exemplary of the endless number of servers that are
15 connected to the Internet.

One server, typically the DC Server 44, but other servers such as Server
10 1 (50), for example, hosts a web-site that includes downloadable software. This software is configured to allow for the placement of contemporaneous audio, typically in the form of voice, and data calls between client and agent.
20

One exemplary software package suitable for the audio call component, that makes the audio (voice) call, is Surf & Call Center™ (VocalTec
25 Communications, Ltd., Herzlia, Israel), having the Surf & Call® software from VocalTec Communications, Ltd., Herzlia, Israel, an embedded plug-in enabling web-to-phone call center applications from a standard web page. The data call
30 can be made via a data collaboration (DC) component, typically in JavaScript or code within an applet, that is typically also on the DC Server 44. For example, one software package with a suitable DC component is a VocalTec® Cosurfer
20 DC Component (from VocalTec Communications, Ltd., Herzlia, Israel), that is typically part of the Surf & Call Center™, detailed above.
35

The DC Server 44 or other server 50 also includes additional JavaScript code for processing the Automatic Number Identification (ANI) as detailed
40 25 below. Once downloaded into the client's PC, the audio call component 60 and the DC Component 61 can, for example, appear on the monitor 31 (JavaScript or code applet not shown).

The audio call component, data call component, JavaScript code, and/or
45 portions thereof can be on different servers and are not restricted to any particular server. Also, these components and portions thereof can be on
30 storage media such as disks, CD's etc., as well as some portions on servers and some portions on storage media.
50

5

Another server, for example, Server 2 52 may serve as an ANI generator, discussed below.

10

5 An implementation of the process of the present invention will now be described. The user or client 20, his browser open, has downloaded software for the placement of contemporaneous voice and data calls along respective voice and data channels between the client 20 and the respective agent 22a-22c. Here, for example, the client 20 has employed the Surf & Call Center™, having the Surf & Call® software, an embedded plug-in, as detailed above, for facilitating an audio IP call between the client 20 and the agent 10 22a-22c. While the Surf & Call® software is shown, other suitable software for this application can be that with the ability to make an Internet Protocol (IP) telephony call from a web browser and the ability to transmit an ANI along with the audio call, the audio call in accordance with standard contemporary telephony.

15

20

25

15 The client 20 has also obtained, typically by downloading, a Cosurfer Data Collaboration (DC) component, such as the VocalTec® Cosurfer DC Component™ (VocalTec Communications, Ltd., Herzlia, Israel), for facilitating the data call to the DC server 44, along with JavaScript code. The JavaScript code functions in distributing the ANI to both the audio call component 60, here, 20 the Surf & Call® software, and the data collaboration component 61, both components 60, 61 appearing as portions on the client's monitor 31.

30

35

Turning also to Fig. 2, the process continues, as an Automatic Number Identification (ANI) is generated in the browser of the client 20, such as in either JavaScript or in a Java applet. An ANI can also be requested from a server with 25 code to reserve ANI's, request sequential numbers, generate random numbers, generate numbers from a database, etc. The resultant ANI need only be such that it is unique to each client, whereby any two clients do not have the same ANI at the same time.

40

45

This ANI serves as a unique identifier of the client's particular coordinated 30 audio and data calls with the selected web-enabled agent in real time. The ANI is a cosurfer identification for the client 20, identifying the client 20 to the telephony system (i.e., in the audio call) and the DC server 44 (i.e., in the data

50

55

5 call), and typically passes through the respective audio and data calls made by the client 20 as a data field.

10 The ANI is a fifteen digit number that conforms to E.164, the specification for telephone numbers, as described in "Numbering Plan For The ISDN Era, Recommendation E.164", CCITT (1991), this document incorporated by
5 reference herein. A number in accordance with this E.164 standard has its first three digits corresponding to a country code, with the remaining twelve digits a
15 National Significant Number.

Here, the first three digits of the ANI are formed, as they are assigned by
10 the same mechanism that generates the ANI, or by another mechanism, such as using a constant value. These first three digits mimic a country code as per the
20 E.164 standard, but are not assigned to any country, as per the E.164 standard, at step 102. The remaining twelve digits are created randomly, via a random
25 number generating program on the PC 30 of the client or via the Internet 24,
15 from a server, such as Server 2 (52), or as otherwise detailed above, at step 104. These numbers are then brought together, at step 106, resulting in the
ANI.

30 At step 108, the ANI is stored in the client's disk (in the client PC 30), typically in a browser cookie. This ANI is stored by means such as JavaScript
20 code. By storing the ANI in a cookie, the next time that an ANI is needed by the client 20, it will come from this cookie, and not from random number generation
35 methods, such as those detailed above.

The JavaScript code then sets the ANI, by copying it and setting one
copy in the audio call component, here the Surf & Call® component (segment 60
40 25 in the screen shot of the client's monitor 31), at step 110; and setting another copy of the ANI in the data call component, here the Cosurfer Data
Collaboration Component Applet (segment 61 in the screen shot of the client's
45 monitor 31), at step 111. These two steps, steps 110 and 111, should be performed contemporaneously and/or in parallel, and preferably, simultaneously.
30 Additionally, the ANI is placed into the data field allotted by telephony specifications to the phone number of the calling party, here the client 20, at
step 110a.

5

10

15

20

25

30

35

40

45

50

With the ANI in the audio call and data call components, the audio call is initiated, at step 114. Here, the audio call initiation is in accordance with the standard H.323 protocol, this protocol being that of the Surf & Call® software. Specifically, audio call initiation with the audio component from the Surf & Call® software is via a Surf & Call® button or icon 62 (Fig. 1), that appears on screen 31 (for example as a pop-up) and is "clicked" (pressed) by a mouse or the like. Moreover, when the Surf & Call Center™ is employed to provide the audio component 60 and the DC component 61, the "clicking" or pressing of the Surf & Call® button or icon 62 starts the DC component 61 attempting to connect to the DC server 44, thus initiating the data call from the client 20, at step 115.

With respect to the audio call, the ANI travels with the audio call through the gatekeeper (GK) 38 so as to connect with the ACD 40 in the PBX 36, at step 116. If there is not a connection with the ACD 40 in the PBX 36, at step 116a, the process stops, until reinitiated by the client 20. At optional step 116a', the audio call is again initiated (step 114 performed again). Once there is a connection with the ACD 40 in the PBX 36, at step 116b, this is a Start Call event, as the ANI is passed with the call to this ACD 40 (with data corresponding thereto ultimately passed to the DC server 44, as detailed below), at step 118.

With respect to the data call, the Cosurfer Data Collaboration (DC) component, typically the applet, connects the client PC 30 to the DC Server 44 at step 115a, typically over a TCP/IP socket link. This connection results in the client 20 data call to the DC server 44, where the ANI and the cosurfing data, including, for example, shared Uniform Resource Locators (URLs) are passed to the DC server 44. Alternately, the DC component can include software programmed such that the start call event also initiates (starts) the above described data call.

These two call initiation steps, steps 114 and 115 should be performed close in time and in parallel, and preferably, simultaneously. This can be done by programming the audio and DC Components to initiate the respective audio and data calls at the times desired.

Once the audio call with the ANI is in the ACD 40, it is routed to the web enabled agent, here one of agents 22a-22c. The ANI and the telephone number

5 (extension number) of the agent 22a-22c also exits the PBX 36 and travels to
the T-server 42, where it is converted to a format recognizable by a CTI Driver
45, such that the ANI and the agent telephone (extension) number can be sent
10 to the CTI driver 45 in the DC server 44. The telephone (extension) number of
the agent 22a-22c, typically serves as the agent's cosurfer Identification, for both
the agent audio call and the agent data call, as detailed below.

15 This CTI driver 45 is programmed to identify the ANI as an identifier for a
data collaboration session, and not a country code, as per the E.164 Standard
(above). The CTI driver then passes the ANI to the DC server 44, along with the
10 number of the party, here the specific agent 22a-22c, to whom the audio (voice)
20 call was connected.

On the agent side, a Cosurfer Data Collaboration (DC) Component,
typically identical to that of the client 20 has been downloaded to the browser of
each agent 22a-22c. Also, the specific agent 22a-22c has transmitted his
25 cosurfer identification, here his telephone (extension) number, that corresponds
to and serves as an identifier for his computer, into the DC server 44, by either
sending it, via a data call, manually or via a conventional program over the
30 Internet 24. As a result of sending his cosurfer identification, each agent is
typically connected to the DC Server 44, via his cosurfer DC component.

20 The DC Server 44 has now received data corresponding to the ANI and
agent telephone (extension) number of the now connected audio call between
client 20 and specific agent 22a-22c. The DC server 44 has also received the
35 ANI from the client's data call, at step 115a, and has also received the agent's
cosurfer identification, here the agent's telephone extension number, as detailed
above. The ANI data (the ANI's) of the client audio component and client data
40 colloboartin component are matched, by convnetinal comparison programs, as
are the telephone (extension) number data (telephone numbers) of the agent
22a-22c audio component and agent data collaboration component.
45 Convnetional matching software then matches the ANI data (ANI) associated
30 with the client Data colloboartion component to the telephone (extension)
number data (telephone number) associated with the agent data colloboration
component. With this match complete, the DC server 44, executes a standard

5 program to connect the client 20 and the specific agent 22a-22c therein,
allowing for the passage of data between the client 20 and the specific agent
10 22a-22c, resulting in the completion of the data call from the client to the
specific web enabled agent 22a-22c, via the Internet 24.

5 This results in a data collaboration session on parallel voice and data
channels, where the client 20 and the web enabled agent (one of 22a-22c) are
15 in voice communication via the audio call (over the audio channel), as well as
browsers coordinated to view same web site and/or page, via the data call (over
the data channel). This data collaboration session allows for the sharing of web
10 documents in conjunction with a voice conversation in real time. Additionally,
the data collaboration session can include guided web browsing, where an
20 agent can guide a customer to a web page, typically by transmitting a Uniform
Resource Locator (URL), joint form handling, where call center agents assist a
customer in filling out a form in real time, text chat, where agents and clients can
25 exchange real time text messages and other similar functions.

Alternately, the present invention may employ an event handler, detailed
in commonly assigned PCT Patent Application entitled: AN IMPROVED AUDIO
30 AND DATA COLABORATION AND COORDINATION SYSTEM, filed on even
date herewith and incorporated by reference herein, as part of the system, as
shown and described in Fig. 1 above. The event handler is typically in the DC
20 server 44. It functions to maintain the cosurfer connection between client 20
and agent 22a-22c in the absence of a browser connection on the client or agent
35 side.

The methods and apparatus disclosed herein have been described with
40 25 exemplary reference to specific hardware and/or software. The methods and
apparatus have been described in a manner sufficient to enable persons of
ordinary skill in the art to readily adapt other commercially available hardware
and software as may be needed to reduce any of the embodiments of the
45 present invention to practice without undue experimentation and using
30 conventional techniques.

While preferred embodiments of the present invention have been
described, so as to enable one of skill in the art to practice the present invention,
50

5

the preceding description is intended to be exemplary only. It should not be used to limit the scope of the invention, which should be determined by reference to the following claims.

10

15

20

25

30

35

40

45

50

55

Claims

5

10

15

20

25

30

35

40

45

50

55

5

What is claimed is:

1. A web enabled call center system comprising:

10

means for placing at least one first cosurfer identifier in at least one audio component for placement in an audio call of at least one sender and at least one data coloboration component for placement in a data call of said at least one sender;

5

15

at least one data collaboration server sever configured for:

receiving first data corresponding to said audio call from said at least one sender to said at least one receiver, said first data including at least said first cosurfer identifier and a second cosurfer identifier from said at least one receiver, said first cosurfer identifier being different than said second cosurfer identifier;

20

10

receiving second data including said first cosurfer identifier, from said data call from said at least one sender;

25

15

receiving third data including said second cosurfer identifier from a data call from said at least one receiver; and

30

processing said first, second and third data, to connect a data call from said at least one sender to at least one receiver, said data call between said at least one sender and said at least one receiver in parallel with said audio call between said at least one sender and said at least one receiver.

20

35

2. The system of claim 1, wherein said addressing server is additionally configured for:

40

25

completing a data call between said addressing server and said receiver once said first cosurfer identifier and said second cosufer identifier have been matched.

45

30

3. The system of claim 1, additionally comprising means for generating an Automatic Number Identification (ANI), said ANI defining said first cosurfer identifier.

50

55

5 4. The system of claim 3, wherein said means for generating an ANI includes
first means for generating a first 3-digit number mimicking a country code and
10 second means for generating a second 12-digit random number.

15 5. A method for conducting a data collaboration session over a wide area
network comprising:

providing a sender with at least one audio component and at least one
15 data collaboration component;

providing a first cosurfer identifier to at least one sender;

10 copying said first cosurfer identifier into said at least one audio
component and said at least one data component;

20 sending said first cosurfer identifier by said at least one audio component,
and a second cosurfer identifier from an intended receiver, said second cosurfer
identifier different than said first cosurfer identifier, in accordance with an audio
25 call between said at least one sender to at least one intended receiver;

15 sending said first cosurfer identifier to said at least one server by said
data collaboration component in accordance with a data call;

30 connecting said data call from said at least one sender to a data call from
said at least one intended receiver, after said intended receiver has transmitted
20 said second cosurfer identifier to said at least one server, such that at least a
portion of said data call between said sender and said at least one intended
35 receiver is in parallel with said audio call between said at least one sender and
said at least one intended receiver.

40 25 6. The method of claim 5, additionally comprising:

providing at least one server, said at least one server including a Data
collaboration server.

45 7. The method of claim 5, wherein said step of providing a first cosurfer
30 identifier to at least one sender includes generating an Automatic Number
Identifier (ANI).

5

8. The method of claim 7, wherein said step of generating said ANI includes generating a 15 digit number.

10

5

9. The method of claim 8, wherein said step of generating a 15 digit number includes:

generating a first three digit number mimicking a country code in accordance with the E.164 telephony standard; and

15

generating a second twelve digit number, to follow said three digit number.

10

20

25

30

35

40

45

50

55




FIG.1




FIG.2

INTERNATIONAL SEARCH REPORT

International application No.
PCT/IL00/00162

A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : H04M 11/00, 3/42

US CL : 379/93.09, 90.01, 201

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 379/93.09, 90.01, 201

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EAST

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5,557,667 A (BRUNO et al) 17 September 1996, col. 1, lines 34-58, col. 2, lines 14-26, col. 5, lines 26-67, col. 6, lines 27-43, and col. 9, line 63 - col. 11, line 40.	1-9
A	US 5,359,645 A (KATZ) 25 October 1994, Abstract, col. 5, lines 32-49, col. 7, lines 32-51, col. 8, line 65 - col. 9, line 29, and col. 10, line 60 - col. 11, line 29.	1-9

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

Q document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

A document member of the same patent family

Date of the actual completion of the international search

20 JUNE 2000

Date of mailing of the international search report

03 JUL 2000

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

LE HIEN LUU

Telephone No. (703) 305-9650

Form PCT/ISA/210 (second sheet) (July 1998)*